

INTERNATIONAL ONE METRE CLASS RIG/SAIL MEASUREMENT FORM

2007

RIGS AND ITS SAILS MEASURED *(cross out as appropriate)*

1

2

3

Hull Registration Number

GENERAL NOTE TO MEASURERS

- 1 Measurements shall be carried out in accordance with the Equipment Rules of Sailing except where varied in the **class rules**.
- 2 The **boat** shall comply with all the **class rules** in Sections D, E, F, G and H even if some of the rules are not mentioned on the measurement form(s).
- 3 This measurement form may be used for up to three **rigs** and its **sails**. Cross out the numbers above for **rigs** and its **sails** which have not been measured. Ring the numbers which have been measured.
- 4 To have more **rigs** and its **sails** added to the **certificate** the **official measurer** shall measure the **rigs** and its **sails** and complete a new rig/sail measurement form. The rig/sail measurement form, together with any re-**certification** fee that may be required and the current **certificate** shall be sent to the owner's **certification authority**.

PARTS

- 1 F.1.1 Does any **rig** comprise more than: one **mast**, one mainsail **boom**, one headsail **boom**, standing **rigging**, running **rigging** and fittings? yes / no

GENERAL

- 2 F.2.3 Do all parts of the rig function in a way that is normal for items of their type? yes / no
- 3 F.2.4(c) Are any ball and/or roller bearings used in any items except for: kicking strap fitting, gooseneck, mainsail boom sheet blocks, headsail boom sheet blocks, headsail boom swivel? yes / no

MAST

- 4 F.3.1(a) Is the principal material of the **spar** aluminium alloy or wood? yes / no
- 5 F.3.1(b) Are other materials on the **spar** limited to: adhesive, paint, powder coat, varnish, wax? NA / yes / no
- 6 F.3.2(b) Is the **spar** section between **upper point** and **lower point**: of circular outer shape and constant except for: internal sail track, local cutaways, openings for fittings and/or **rigging**, internal and/or external **spar** joiners? yes / no
- 7 F.3.3(a) Are the fittings listed in class rule F.3.3(a) present? yes / no
- 8 F.3.3 Are there any fittings except items listed in class rules F.3.3(a) & (b)? yes / no
- 9 F.3.3(c)(2) Do the mainsail boom **spar** and the kicking strap have pivot points aft of the mast **spar** in the regions adjacent to these points? yes / no
- 10 F.3.4 Is the **lower point** to **upper point** dimension correct?
rig 1 1600 mm max rig 2 1180 mm max rig 3 880 mm max yes / no
- 11 F.3.4 Is the lower edge of the headsail stay **limit mark** at the foreside of the **spar** to the **upper point** dimension correct?
rig 1 220 mm min rig 2 160 mm min rig 3 120 mm min yes / no
- 12 F.3.4 Does the height of checkstay **rigging point** above the **heel point** exceed 100 mm? NA / yes / no
- F.3.4 Between **lower point** and **upper point**:
- 13 (1) Is the diameter of the **spar** less than 10.6 mm? yes / no
- 14 (2) Does the difference between the largest and smallest diameters exceed 0.3 mm? yes / no
- 15 F.3.4 Does the length of any **spar** joiner exceed 100 mm? yes / no
- 16 F.3.4 Does the total length of cutaways between the **lower point** and **upper point** exceed 100 mm? yes / no
- 17 F.3.4 Is the width of all **limit marks** between 3 and 10 mm? yes / no

BOOMS

- 18 F.4.1(a) Is the principal material of the **spars** aluminium alloy or wood? yes / no
- 19 F.4.1(b) Are other materials on the **spars** limited to: adhesive, paint, powder coat, varnish, wax? NA / yes / no
- 20 F.4.2 Is the section of **spars** constant except for the last 10 mm at each end and openings for fittings and rigging? yes / no
- 21 F.4.3-4 Are the fittings listed in class rules F.4.3(a) and F.4.4(a) present? yes / no
- 22 F.4.3-4 Are there any fittings except items listed in class rules F.4.3 & F.4.4? yes / no
- F.4.5 Ignoring the last 10 mm at each end and openings for fittings and rigging:
- 23 Does the largest external dimension exceed 20 mm? yes / no
- 24 Does the difference between the smallest and largest value along the **spar** of any external dimension exceed 0.5 mm? yes / no

STANDING RIGGING

- 25 F.5.1 Except for terminations and the headsail boom swivel, are there any materials except steel and/or polymer? yes / no
- 26 F.5.2(a) Is the standing **rigging** listed in class rule F.5.2(a) present? yes / no
- 27 F.5.2-3 Is there any standing **rigging** except items listed in class rules F.5.2 and F.5.3? yes / no

RUNNING RIGGING

- 28 F.6.2(a) Is the running **rigging** listed in class rule F.6.2(a) present? yes / no
- 29 F.6.2-3 Is there any running **rigging** except items listed in class rules F.6.2 and F.6.3? yes / no

MAINSAILS

- 30 G.2.2(b) If the **sails** have been certified by the manufacturer awarded with a special licence, indicate here and ignore steps 31 to 58. yes / no
- 31 G.3.1(a)(1) Are all sails **soft sails** and **single ply sails**? yes / no
- 32 G.3.1(a)(2) Does the **body of the sail** consist of the same **ply** throughout and not more than four parts joined by **seams**? yes / no
- 33 G.3.1(a)(3) Do seams deviate by more than 10 mm from a straight line between **luff** and **leech**? yes / no
- 34 G.3.1(a)(4) Does each **sail** have three **batten pockets**, or battens if there are no **batten pockets**, at the leech? yes / no
- 35 G.3.1(a)(5) Does the **leech** extend aft of straight lines between: adjacent batten pocket points, **sail corner measurement points** and nearest batten pocket points? yes / no
- 36 G.3.1(a)(6) Does the **foot** extend below a straight line between **tack point** and **clew point**? yes / no
- 37 G.3.1(a)(7) Is a class insignia present? yes / no
- 38 G.3.1(b) Are there any parts except items listed in class rule G.3.1(b)? yes / no
- 39 G.3.2(a) Are the parts of the **sails** joined or added using only welding; gluing; bonding with self-adhesive tapes/materials; stitching? yes / no
- 40 G.3.2(b) Except for stitching, does the method used to join the **seams** extend beyond the edges of the **seams**? yes / no
- 41 G.3.3 Does the upper batten exceed 10 mm wide x 75 mm long, and/or its **batten pocket** exceed 25 mm wide x 95 mm long? yes / no
- 42 G.3.3 Do the other battens exceed 10 mm wide x 100 mm long, and/or their **batten pockets** exceed 25 mm wide x 120 mm long? yes / no
- G.3.3 Are the following **primary sail dimensions** within the permitted ranges?
- | | | | | | |
|----|----------------------------|----------------|----------------|--------------|----------|
| 43 | Leech Length | 1 1610-1620 mm | 2 1200-1210 mm | 3 910-920 mm | yes / no |
| 44 | Foot Length | 1 350-360 mm | 2 340-350 mm | 3 310-320 mm | yes / no |
| 45 | Quarter Width | 1 305-315 mm | 2 295-305 mm | 3 265-275 mm | yes / no |
| 46 | Half Width | 1 235-245 mm | 2 225-235 mm | 3 205-215 mm | yes / no |
| 47 | Three-Quarter Width | 1 135-145 mm | 2 130-140 mm | 3 115-125 mm | yes / no |
- G.3.3 Are the following exceeded?
- | | | | |
|----|---|--------|---------------|
| 48 | Top width | 20 mm | yes / no |
| 49 | Primary & secondary reinforcement from nearest sail corner measurement point | 125 mm | yes / no |
| 50 | Secondary reinforcement for flutter patches | 50 mm | NA / yes / no |
| 51 | Secondary reinforcement at luff fittings , luff slides and/or luff openings | 20 mm | NA / yes / no |
| 52 | Tabling width | 15 mm | yes / no |
| 53 | Seam width | 15 mm | yes / no |
| 54 | Seam to nearest sail corner measurement point | 150 mm | yes / no |
| 55 | Batten pocket point, as in G.2.4, to the nearest leech point | 20 mm | yes / no |
| 56 | Largest cringle dimension | 10 mm | yes / no |
| 57 | Except for luff slides the largest luff fitting dimension | 10 mm | NA / yes / no |
| 58 | Sail shape indicator stripe width | 30 mm | NA / yes / no |

HEADSAILS

- 59 G.2.2 (b) If the **sails** have been certified by the manufacturer awarded with a special licence, indicate here and ignore steps 60 to 83. yes / no
- 60 G.4.1(a)(1) Are all sails **soft sails** and **single ply sails**? yes / no
- 61 G.4.1(a)(2) Does the **body of the sail** consist of the same **ply** throughout and not more than three parts joined by **seams**? yes / no

62	G.4.1(a)(3)	Do seams deviate by more than 10 mm from a straight line between luff and leech ?			yes / no		
63	G.4.1(a)(4)	Does the leech extend aft of a straight line between the aft head point and clew point ?			yes / no		
64	G.4.1(a)(5)	Does the foot extend below a straight line between tack point and clew point ?			yes / no		
65	G.4.1(b)	Are there any parts except items listed in class rule G.4.1(b)?			yes / no		
66	G.4.2(a)	Are the parts of the sails joined or added using only welding; gluing; bonding with self-adhesive tapes/materials; stitching?			yes / no		
67	G.4.2(b)	Except for stitching, does the method used to join the seams extend beyond the edges of the seams ?			yes / no		
68	G.4.3	Does any batten exceed 10 mm wide x 75 mm long, and/or its batten pocket exceed 25 mm wide x 95 mm long?			NA / yes / no		
	G.4.3	Are the following sail dimensions within the permitted ranges?					
		Luff Length					
69	1	1320-1330 mm	2	980-990 mm	3	730-740 mm	yes / no
		Leech Length					
70	1	1245-1255 mm	2	900-910 mm	3	655-665 mm	yes / no
		Foot Length					
71	1	375-385 mm	2	340-350 mm	3	290-300 mm	yes / no
		Half Width					
72	1	185-195 mm	2	165-175 mm	3	140-150 mm	yes / no
73		Clew point to lower batten pocket point					
	1	400-430 mm	2	285-315 mm	3	205-235 mm	NA / yes / no
74		Clew point to upper batten pocket point					
	1	820-850 mm	2	590-620 mm	3	425-455 mm	NA / yes / no
	G.4.3	Are the following exceeded?					
75		Top width		20 mm			yes / no
76		Primary & secondary reinforcement from nearest sail corner measurement point		125 mm			yes / no
77		Secondary reinforcement for flutter patches		50 mm			NA / yes / no
78		Secondary reinforcement at headsail stay slides and/or loops		20 mm			NA / yes / no
79		Tabling width		15 mm			yes / no
80		Seam width		15 mm			yes / no
81		Seam to nearest sail corner measurement point		100 mm			yes / no
82		Largest cringle dimension		10 mm			yes / no
83		Sail shape indicator stripe width		30 mm			NA / yes / no

DECLARATION BY THE OWNER

To the best of my knowledge, the aluminium alloys used for the mast and boom **spars** are of the grades listed in F.3.1 and F.4.1 and the wall thickness tolerances in F.3.4 and F.4.5 are complied with.

Signature

Date

.....

.....

MEASURER'S COMMENTS

If the **official measurer** has any doubt concerning the application of, or compliance of any part of the **boat** with the **class rules** he shall report it on the measurement form(s) before sending them to the **certification authority** and not sign measurement form(s) or sails.

DECLARATION BY THE MEASURER

I confirm that I have taken the measurements on this form, that the particulars on this form are correct and that, to the best of my knowledge, the **boat** complies with the rules covered by this form. I have stated above in MEASURER'S COMMENTS those points where I have any doubt concerning the application of, or compliance of any part of the **boat** with, the class rules whether or not they are covered by the measurement form.

Name of Measurer
(BLOCK CAPITALS)

Officially recognised by
(ISAF Member National Authority of Country)

.....

.....

Signature

Date

.....

.....